

ELECTRODE OVEN


EOB-5-RM / EOB-10-RM – MILD STEEL
EOB-5-RS / EOB-10-RS – Stainless Steel



EOB-5-RM-MT & EOB-10-RM-MT
MAGNET TYPE – MILD STEEL



EOB-5-RM-MT &
EOB-10-RM-MT - Connection



POWER CONNECTIONS



EOC-5-RM &
EOC-10-RM



EO-TC-5B & EO-TC-10B
- TEMP CONTROLLED



EO-TC-5C & EO-TC-10C
-TEMP CONTROL & GAUGE



EO-TC-5T & EO-TC-10T
Temperature Control / Gauge



MILD Steel
EOB-5-RM
EOB-10-RM

STAINLESS
EOB-5-RS
EOB-10-RS

EOB-5-RM-MT &
EOB-10-RM-MT
MAGNET Type / Mild Steel

EOC-5-RM & EOC-10-RM –
- Inner Body of Mild Steel

Model	EOB-5-RM(RS)	EOB-10-RM(RS)	EOB-5-RM-MT	EOB-10-RM-MT	EOC-5-RM	EOC-10-RM
Electrode Capacity	5 KG	10 KG	5 KG	10 KG	5 KG	10 KG
Input Voltage	AC220V/230V AC.DC.60-110V		AC.DC 60V-110V		AC220V AC.DC.60-120V	
Power	238W /50W-100W	238W/100W-195W	50W – 100W	238W	205W	238W
Max. Temperature	150Deg C+/- 15 Deg C		150 Deg C		150 Deg C	
Electrode Length	450 mm		450 mm		450 mm	
Chamber Size			Dia 80x(430+35)H	Dia 110x(420+50)H	D 86x485H	D 108x485H
Overall Size (L x W x H)	168x188x610mm	202x232x615mm	D 196x635H	D230x620H	D 162x697H	D 185x697H
Weight	2.9 Kg	4.2 Kg	3.2 Kg	5.0 Kg	3.8 Kg	4.2 Kg

EO-TC-5B & EO-TC-10B –
- Temp Control – 200 Deg C

EO-TC-5C & EO-TC-10C
Temperature Control &
Gauge – 150 Deg C

EO-TC-5T & EO-TC-10T
Temperature Control / Gauge /
Stainless Steel / 300 Deg C

Model	EO-TC-5B	EO-TC-10B	EO-TC-5C	EO-TC-10C	EO-TC-5T	EO-TC-10T
Electrode Capacity	5 KG	10 KG	5 KG	10 KG	5 KG	10 KG
Input Voltage	AC220V / 230V		AC220V / 230V		AC220V	
Power	238W	238W	205W	238W	800W	
Max. Temperature	50 Deg C – 200 Deg C		50 Deg C – 150 Deg C		50 Deg C – 300 Deg C	
Electrode Length	450 mm		450 mm		450 mm	
Chamber Size			D 86x465 H	D 108x465 H		
Overall Size (L x W x H)	D196 x 635 H	D 230 x 646 H	145x200x590	210x167x590	190x230x660	250x190x700mm
Weight	2.9 Kg	5.1 Kg	3.8 Kg	4.2 Kg	4.6 Kg	5.0 Kg

AUTHORISED DISTRIBUTOR