

MIG TORCHES & PARTS

(OTC® Compatible)

TORCHES



MODEL NOS:


Power at 60%
CO2 - MIX

TW18C	180A – 150A
TW20C	230A – 200A
TW30C	280A – 240A
TW35C	400A – 360A
TW50C	500A – 420A

Length : 3, 4, 5, 6 Mtrs Long

Connections : OTC® Type/Euro/Miller®/Panasonic® etc

CONNECTION OPTIONS



INDEX

A	OTC® Connection using OTC® Liner
B	EURO Connection using EURO Liner
C	EURO Connection using OTC® Liner

DESCRIPTION

SWAN NECK



PART NO

PART NO	TORCH
1 SN-20C	TW18C, TW20C
2 SN-30C-M	TW30C
3 SN-35C-M	TW35C
4 SN-50C-M	TW50C
5 SN-35C-S	TW35C
6 SN-50C-FX	Flexible, 350A, 500A
7 SN-35C-BR	TW-35C
8 GD-3B-S	(Using Tip Holder Bernard)

TIP HOLDER



PART NO

PART NO	TORCH
11 TH-30C-F	TW30C
12 TH-35C-F	TW35C
13 TH-50C-F	TW50C
14 TH-35C-F-Cu	TW-35C (Copper Material)

TORCH

INSULATOR TUBE



PART NO

PART NO	TORCH
41 IT-180P	TW180P, 230P
42 IT-350P	TW300P, TW350P
42 IT-350P-HD	TW300P, TW350P
44 IT-350P-B	TW300P, TW350P
44 IT-350P-B-HD	TW300P, TW350P
45 IT-500P	TW-500P
45 IT-500P-HD	TW-500P
47 IT-500P-B	TW-500P
47 IT-500P-B-HD	TW-500P
48 IT-350P-CC	TW300P, TW350P
49 IT-500P-CC	TW-500P

50 WS-IT-350 Washer for IT-350P-B
53 WS-IT-500P Washer for IT-500P-B

GAS NOZZLE 180A/500A



PART NO

PART NO	LENGTHxID(mm)
21 GN-180P-F	75.5 x 13
22 GN-180P-IN	75.5 x 13
23 GN-20C-F	77.5 x 15
26 GN-20C-C	77.5 x 13
24 GN-500P-F	84.0 x 19
25 GN-500P-C	84.0 x 16

LENGTHxID(mm)

GAS NOZZLE 350A/300A



PART NO

PART NO	LENGTHxID(mm)
31 GN-350P-F	73.0 x 16
32 GN-350P-F2	73.0 x 16
GN-350P-F2-S	71.0 x 16
33 GN-350P-C	73.0 x 13
34 GN-350P-C2	73.0 x 13
35 GN-350P-F-VT	73.0 x 16 (2.5mm Thick)
36 GN-350P-L	100.0 x 10
37 GN-350P-BN	73.0 x 10

SPECIAL PARTS



PART NO

PART NO	TORCH
91 TH-35C-F-R	TW350P x F Thread
92 GN-350P-F-R	70.0 x 16 (2.5 mm Thick)
93 IT-350P-B-HD-R	TW350P
94 TH-35K-F	TW350P
95 IT-350-K-HD	TW350P

TORCH

CONTACT TIPS & GAS DIFFUSOR



PART NO

PART NO	TORCH
51 GD-350P	TW300P, TW350P
52 GD-500P	TW500P
61 CE-45-0.6 to 1.6	E-Cu for all Models
CZ-45-0.6 to 1.6	CuCrZr for all Models
62 CT-269.5-D0.8	CuCrZr for all Models

Contact Tips are also available in CuCrZr (Cz-45...)
Contact Tips are avlbl in size from 0.6 to 1.6 mm
Lengths available – 40mm, 42mm, 45mm & 69.5mm

TORCH

STEEL LINERS



PART NO

PART NO	I.D.XO.D.xL
71 LI-18C-3	TW18C, 20C, 30C (Blue)
72 LI-35C-3	TW30C, 35C (Red)
LI-35C-3-BK	TW30C, TW35C (Black)
73 LI-50C-3	TW50C (Yellow)

I.D.XO.D.xL

Liners are available in Length of 3.5 M, 4.5 M, 6.1 M respectively in all Types

TEFLON LINERS



PART NO

PART NO	I.D.XO.D.xL
81 LI-T-C-8.1x3	1.5x4.5x3.5M (Blk)
82 LI-T-C-8.3x3	2.5x4.5x3.5M (Grey)
83 LI-T-C-9.1x3	1.5x4.2x3.5M (Blue)
84 LI-T-C-9.2x3	2.2x4.2x3.5M (Red)
85 LI-T-C-9.3x3	3.0x4.5x3.5M (Ylw)

I.D.XO.D.xL

Liners are available in any Length as desired for all Types