

MIG TORCHES & PARTS

(Tregaskiss® Compatible)

TORCHES



MODEL NOS:

Power at 60%
CO2 - MIX

TW-333R x 4.5-RE 280A – 240A
TW-444R x 4.5-RE 400A – 360A
TW-555R x 4.5-RE 500A – 420A

Length : 4.5 M or as Required

Rear End Connections : Tregaskiss®/Euro/Bernard®/
Hobart®/Tweco® etc as Required

Process: MIG/MAG

Method of Guidance: Manual

Type of Cooling: Air

Diameter Range of Solid Wire: D1.0 – 1.4

and Flux cored Wire: D1.6 – 2.4



PART NO	REF
1 CT-S-1.0R	403-10
2 CT-S-1.2R	403-45
3 CT-S-1.3R	403-52
4 CT-S-1.6R	403-116



PART NO	REF
11 CT-H-1.0R	403-1-10
12 CT-H-1.2R	403-1-45
13 CT-H-1.3R	403-1-52
14 CT-H-1.6R	403-1-116
15 CT-TL-0.8R (to 1.6R)	403-20-0.8 (0.9,1.0,1.2,1.4, 1.6)



PART NO	REF
21 GN-438-R	401-4-38
22 GN-450-R	401-4-50
23 GN-462-R	401-4-62
24 GN-475-R	401-4-75
25 GN-4250-R	401-42-50



PART NO	REF
31 GN-550-R	401-5-50
32 GN-562-R	401-5-62
33 GN-575-R	401-5-75
41 GN-650-R	401-6-50
42 GN-662-R	401-6-62
43 GN-675-R	401-6-75



PART NO	REF
54 GD-43-R	404-3
53 GD-430-R	404-30
58 GD-420-R	404-20



PART NO	REF
61 SN-3R-45	305-45
62 SN-3R-60	305-60
64 SN-4R-45	405-45
65 SN-4R-60	405-60
67 SN-5R-45	505-45
68 SN-5R-60	505-60

69 SN-4R-AS AUTO-STRAIGHT



PART NO	REF
71 SW-42-RR	402-2
72 SW-45-R	402-5
73 SW-45-R-2	402-5



PART NO	REF(IDxODxL)
81 LI-1.9R-4.5	1.9x4.5x5.0mm
82 LI-2.2R-4.5	2.2x4.8x5.0mm
83 LI-2.2R2-4.5	2.2x4.8x5.0mm

** Other Lengths are also available